

42U Vertical 24 Schuko Socket PDU w/ 2x16A Circuit Breaker & 2MT 3x4 mm² Cable 32A CEE PLUG

DESIGN & MATERIAL

Plastic Material	Fire Retardant Nylon 6 v0 or v2
Body Material	Aluminum Body
Sockets	2x12 Schuko (DIN49440)
Cable Options	1,5 Mtr / 1,8 Mtr / 2 Mtr / 3 Mtr / 5 Mtr 3x2,5 mm ² / 3x4 mm² / 3x6 mm ² / 5x2,5 mm ²
Rack Mount	Verical Rack Mountable – Rotating Installation Ears
Contacts	Contacts:Brass
Protection	2x16A Circuit Breaker Surge Protector On/Off Switch
Certificate	CE
Warranty	Lifetime (On production based defects)

ELECTRICAL & ENVIROMENTAL

Cable Plug Type Options	CEE NORM 32A (EN60309) UK 13A (BS1363) UPS(FRENCH) SCHUKO (GERMAN/DIN 49440) IEC 320 (C14&C20)
Max. Output power	7000W (220-240V)
Nominal Input Voltage	100-240VAC
Max. Total Current Draw	32A
Operable Humidity	% 5-95
Operable Temperature	-5°C to +45°C
Storage Temperature	-25°C to +65°C

Highlights

- Rack Mountable
- Rotating Installation Ears
- Aluminum Body
- Fire-retardant plastic material
- Rotating Installation Ears
- Fuse Box designed to prevent accidental shutdowns
- Mounting ears create isolation between rack cabinets and PDU
- Arc flash proof sockets
- Earthing contacts are TSD and BDE German standard
- 100% Brass socket contacts
- Design Certification

The Package Includes

- PDU
- Screw&Nut Set for installation

Options

- Surge Protect
- Cable Length/Plug type on demand
- 3/6/9/12 Way Options
- Voltmeter / Ammeter
- Color Options

